



# FLUIDMATIC IIIG

## Automatic Transmission Fluid

### PERFORMANCES LEVELS

#### Meets the requirements

- ✓ GM Dexron IIIG / IIIH
- ✓ Ford Mercon

#### Suitable for

- ✓ ZF TE-ML 14A
- ✓ Allison C4

### APPLICATIONS

- FLUIDMATIC IIIG is an automatic transmission fluid that meets GM Dexron® IIIG and Ford Mercon® standards.
- This lubricant is formulated with premium base stocks and carefully selected additives to meet the challenging demands of an automatic transmission environment. FLUIDMATIC IIIG is a well balanced fluid for heavy duties and passenger cars equipped with automatic transmissions thanks to friction modifiers, detergent dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents
- FLUIDMATIC IIIG is a high-quality friction-modified lubricant previously qualified by both General Motors and Ford.

### CUSTOMER BENEFITS

- **Standard drain interval:** it depends on the automatic gearboxes and the application. The lubricant keeps an efficient operation over the fill life.
- **Special friction properties:** Smooth gear shifting without shudder.

TOTAL LUBRIFIANTS – Immeuble Spazio  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

FLUIDMATIC IIIG

Update: 07/2017



- **Excellent oxidation stability:** it avoids the deterioration of its properties thanks to an adapted antioxidant and detergent level.
- **Effective Low Temperature Fluidity:** it avoids surge or sudden overload of circuits when starting in very cold weather.
- **Excellent elastomers compatibility:** it prevents oil leakage.

## PHYSICAL AND CHEMICAL CHARACTERISTICS

FLUIDMATIC IIIG	Unit	Method	Value
Colour	-	ASTM D1500	Red
Density at 15°C	kg/m <sup>3</sup>	ASTM D4052	849,8
Kinematic Viscosity at 40 °C	mm <sup>2</sup> /s	ASTM D445	33,73
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	7,296
Brookfield Viscosity at -40°C	cP	ASTM D2983	9548
Viscosity Index	-	ASTM D2270	190
Pour Point	°C	ASTM D97	-51
Flash Point	°C	ASTM D92	208

*\*The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*

## RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C while avoiding exposure to strong sunlight, extreme cold or high temperature variations.

All packages should be protected from bad weather conditions. Otherwise, the drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

TOTAL LUBRIFIANTS – Immeuble Spazio  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

FLUIDMATIC IIIG

Update: 07/2017



*This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.*

## HEALTH, SAFETY AND ENVIRONMENT

---

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. The information is accessible on request from your local dealer or on the website [www.quickfds.com](http://www.quickfds.com).

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.

TOTAL LUBRIFIANTS – Immeuble Spazio  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

FLUIDMATIC IIIIG

Update: 07/2017



*This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.*