DYNATRANS DA 85W90

Data sheet

Oil for limited slip differentials self blocking axles

APPLICATIONS

Limited slip differentials

- Oil specially adapted to the lubrication of self-blocking axles equipped with limited self-differentials.

PERFORMANCES

International Specifications

- API GL-5
- ZF TE-ML 05C,12C

Level

- MIL-L-2105D

CUSTOMER BENEFITS

Technical Profile

- High viscosity index
- Very high extreme-pressure properties
- Specific friction properties
- High thermal stability
- Excellent oxidation resistance, anti-wear, antifoam and antirust properties

CHARACTERISTICS

Total Dynatrans DA	Method	Units	SAE Grade 85W90
Volumetric mass at 15°C	ASTM D1298	Kg/m^3	906
Viscosity at 40°C	ASTM D445	mm^2/s	162
Viscosity at 100°C	ASTM D445	mm^2/s	17
Viscosity index	ASTM D2270	-	108
Flash point Cleveland	ASTM D97	°C	188
Pour point	ASTM D92	°C	-15

The typical characteristics mentioned represent mean values.

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards.
A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.