

SPIRIT WBF 5400



Metalworking

Multifunctional micro-emulsion for a wide range of metals.

APPLICATIONS

- **SPIRIT WBF 5400** is recommended for workshops where there are wide variety of machining operations and materials.
- **SPIRIT WBF 5400** is particularly well adapted to difficult machining operations.
- **SPIRIT WBF 5400** is suitable for machining ferrous and non ferrous metals.
- **SPIRIT WBF 5400** gives very good results for flat, cylindrical and centreless grinding.
- Recommended rate of use:
 - grinding: 4 %
 - light machining: 5 to 7 %
 - heavy machining: 6 to 9 %.

SPECIFICATIONS

ISO 6743/7

- ISO-L MAE

ADVANTAGES

- **SPIRIT WBF 5400** is very easy to use, simply by pouring it into good quality water.
- Excellent cooling and lubricant power.
- Efficient protection of machined parts and machines against corrosion.
- Good mechanical performances, providing:
 - Reduced cutting efforts
 - Extended tool lifetime
 - Very good surface finish to parts.
- Properties in service:
 - Excellent stability over time increases drain intervals;
 - Cuttings have a low rate of humidity;
 - Good anti-foaming properties.
- It resists the development of bacteria and mould very well, thus it is more environmentally and operator friendly.
- Very multifunctional
- Low smell

HEALTH AND SAFETY

- Does not contain: formaldehyde liberators or boron.
- Is free of: chlorine, DEA, nitrite and phenol.

TOTAL LUBRICANTS
Industry & Specialties
18-09-2013 (supersedes 12-04-2011)
SPIRIT WBF 5400
1/2



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.



TYPICAL CHARACTERISTICS	METHODS	UNITS	SPIRIT WBF 5400	
			CONCENTRAT E	EMULSION AT 5%
Density at 15°C	ISO 3675	kg/m ³	979	
Kinematic viscosity at 40°C	ISO 3104	mm ² /s	27	9.5
pH at 5%	NF T 60 193			
Refractometric factor			1.2	

Above characteristics are mean values given as an information.

RECOMMENDATIONS FOR USE

- To ensure good conservation of the fluid's properties through time and thus increase its lifetime, we recommend:
 - Regular monitoring of the concentration of the bath with a refractometer. Do not forget to multiply the reading value by the refractometric factor.
 - Regular monitoring of the pH of the emulsion and the hardness of the water.
- Total offers its clients a regular laboratory fluid analysis service: *SOLUBLE CHECK*.
Get in touch with your sales contact to obtain further information.
- Before using any fluid for the first time or before each change, we recommend cleaning the machine with a specific cleaning product: *CONTRAM CB 3*.
- If punctual top-ups of Biocide are required, Total offers an efficient product: *EBOTEC BT 80*.

Your sales and technical contacts are ready to provide you further information.